

# Wall mounted unit

FTXTM-A + RXTM-A



perfera



-30°

Guaranteed operation down to -30°C



Fireplace logic



Weather compensation function



Heat boost



Onecta app

## Attractive, wall mounted design with perfect indoor air quality down to -30°C

- › Guaranteed heating operation down to -30°C
- › Keeps properties warm inside when outdoor temperatures drop
- › Comfort+: perfect comfort with homogeneous temperature
- › Seasonal efficiency values up to A+++ in cooling and heating
- › Even temperature distribution thanks to fireplace logic
- › Heat boost: fast heating during start-up (pair only)
- › 2 area motion detection sensor
- › Purifies the air of viruses, bacteria and fine dust
- › Daikin Flash Streamer technology: powerful air purification
- › Silver allergen removal and air purifying filter
- › Voice control
- › Onecta app
- › Quiet in operation: down to 19dBA sound pressure level
- › 3-D airflow: air is blown into all corners of a room

# FTXTM-A + RXTM-A



Efficiency data		FTXTM + RXTM		30A + 30A		40A + 40A			
Cooling capacity	Min./Nom./Max.	kW		1.2 / 3 / 4.6		1.2 / 4 / 5.2			
Heating capacity	Min./Nom./Max.	kW		0.8 / 3.2 / 7.4		0.9 / 4 / 8.8			
Power input	Cooling	Nom.		0.58		0.85			
	Heating	Nom.		0.6		0.73			
Space cooling	Energy efficiency class			A+++					
	Capacity	Pdesign		kW		3			
	SEER				8.65		8.95		
	Annual energy consumption			kWh/a		121			
Space heating (Average climate)	Energy efficiency class			A+++					
	Capacity	Pdesign		kW		3			
	SCOP/A				5.35		5.5		
	Annual energy consumption			kWh/a		785			
Space heating (Cold climate)	Energy efficiency class			A+					
	Capacity	Pdesign		kW		4.38			
	Annual energy consumption		kWh/a		2,176		2,639		
	SCOP/C				4.23		4.42		
Nominal efficiency	EER				5.13		4.71		
	COP				5.3		5.51		
	Annual energy consumption			kWh		292		425	
	Energy labeling	Cooling/Heating Directive		A/A					
Current - 50Hz	Maximum fuse amps (MFA)		A		16				

Nominal heating capacities are based on: indoor temperature: 20°CDB, outdoor temperature: 7°CDB, 6°CWB, equivalent refrigerant piping: 5m, level difference: 0m. | Nominal cooling capacities are based on: indoor temperature: 27°CDB, 19°CWB, outdoor temperature: 35°CDB, equivalent refrigerant piping: 5m, level difference: 0m. | See separate drawing for operation range

Indoor unit		FTXTM		30A		40A	
Dimensions	Unit	HeightxWidthxDepth		mm		298 x 804 x 252	
Weight	Unit			kg		12	
Air filter	Type	Removable / washable					
Fan	Air flow rate	Cooling	Silent operation / Low / Medium / High	m³/min		4.8 / 5.6 / 8.1 / 13.2	
		Heating	Silent operation / Low / Medium / High	m³/min		4.7 / 5.6 / 7.7 / 11.7	
Sound power level	Cooling			dBA		60	
	Heating			dBA		59	
Sound pressure level	Cooling	Silent operation / Low / High		dBA		21 / 25 / 45	
	Heating	Silent operation / Low / High		dBA		19 / 22 / 43	
Control systems	Infrared remote control		ARC466A83				
	Wired remote control		-				

Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data

Outdoor unit		RXTM		30A		40A	
Dimensions	Unit	HeightxWidthxDepth		mm		605 x 930 x 376	
Weight	Unit			kg		42	
Sound power level	Cooling			dBA		60.0	
	Heating			dBA		60.0	
Sound pressure level	Cooling	Nom.		dBA		48.0	
	Heating	Nom.		dBA		49.0	
Operation range	Cooling	Ambient	Min.~Max.	°CDB		-10 ~46	
	Heating	Ambient	Min.~Max.	°CWB		-31 ~18	
				°CDB		-30 ~24	
Refrigerant	Type			R-32			
	GWP			675.0			
	Charge			kg / tCO2Eq		0.97 / 0.66	
Piping connections	Liquid	OD		mm		6.35	
	Gas	OD		mm		9.50	
	Piping length	OU - IU	Max.	m		20	
	Additional refrigerant charge			kg/m		0.02 (for piping length exceeding 10m)	
	Level difference	IU - OU	Max.	m		15.0	
Power supply	Phase/Frequency/Voltage		Hz/V		1~/50 / 220-240		
Current - 50Hz	Maximum fuse amps (MFA)		A		16		

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · België · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende



ECPEN24-064

10/2024



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: [www.eurovent-certification.com](http://www.eurovent-certification.com)

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.